



MAJORLITE

LED

Type D Sign Light

230V

ML-D-LED230

Specification:

Conforms to BS EN 12899-1:2007

Case material: Aluminium, powder coated grey or black as standard
 Lens material: High impact frosted PETG hinged lens
 Ingress protection: IP56
 Corrosion resistance: SP1
 Fixings: Anti-corrosion & anti-rotational

Mounting options: Standard outreach ~~650mm~~ **825mm**.
 Bracket arm options available for 89, 140, 168mm posts
 Bespoke mild steel electroplated bracketry

Compatibility: Photocell (optional)
 CMS / DALI (optional)

Gear Tray: High performance LED driver,
~~24~~ **10** LED gear tray complete with quick connect plug + socket

Nominal life expectancy: 50,000+ hrs.

Voltage: 230 VAC

Power consumption: ~~24.5w~~ **TBA**

Power factor correction: ~~≥0.94~~ **TBA.**


Colour rendering index: RA60

Charge code:

Recyclable: Yes

Warranty: www.mallatite.co.uk/certificates-warranty

Maintenance: Clean external surfaces with diluted mild detergent as required, paying particular attention to the lens and photocell window.



Lighting performance (1500 x 1500mm)

Mean illuminance: E2

Uniformity of illuminance: ~~UE1~~ **UE2**