



DS75 Street Screen Portfolio

Amscreen is a leading provider of screen solutions in Europe offering seamless, scalable deployments & support via our full service approach & RDM®



Suitable for: Outdoor Bus Shelter | Outdoor Free Standing | Single (Poster Option) / Dual Screen

A Full Service Screen Solution



RDM® - Remote Device Monitoring



OptimEyes Audience Analytics



Single & Double Sided Options



Ease of Install & Maintenance

Screen Hardware Summary



High Impact

Weatherproof, high bright displays bringing content alive whatever the weather



Distribution & Scalability

European production and plug and play design gives speed and flexibility



Ease of Install & Maintenance

Bespoke modular designs and jigs offer fast, non-disruptive installs and maintenance



Security & Future Proofed

Secure system via encryption and authentication protocols plus ease of leveraging new tech.

Software Summary



Smart Tracking & Sensors

Smart brightness® and optional audience tracking using leading tracking platform, OptimEyes via Quividi



Host Integration & Remote Management

Integration with host systems such as Ayuda, Scala, Broadsign etc & RDM® provision

Service Summary



RDM® Remote Smart Management

Alerts and automated data collection via unique system architecture



RDM® Remote Smart Maintenance

Integrated asset management and trouble ticketing to facilitate remote fixes



DS75 Street Screen Portfolio

DS75 Bus Shelter

Single/Dual Sided

High impact versatile sign integrating with existing structures



Single (digital) sided display with rear backlit poster option

Dual (digital) sided display variant

Bus Shelter integration

Audience analytic camera on digital sides

Height: 2,261mm
Width: 1,336mm
Depth: 305mm
Note: all dimensions +/- 7mm

Weight: 400 to 420Kg

DS75 FSU

Single/Dual Sided

Super sized sign for maximum high street visibility



Single (digital) sided display with rear backlit poster variant

Dual (digital) sided display variant

Free standing

Provision for mains consumer panel

Height: 2,850mm
Width: 1,336mm
Depth: 305mm
Note: all dimensions +/- 7mm

Weight: 500 to 520Kg

Screen Specifications



The Displays

- 2500 nit 75 inch LCD panel
- 1080 X 1920 pixels
- Direct sunlight visible
- 9:16
- 5000:1 contrast ratio
- 16.7m display colours
- LED auto-brightness
- Smart Brightness® backlight control



Connectivity

- 4G multi network
- RDM® Remote Smart Management option
- 3rd party monitoring system options



Enclosure

- 9.5mm laminated glass
- Double side screen option
- Backlit rear poster option
- Modular field serviceable



Conformance

- CE (RED, LVD, EMC)
- RoHS and WEEE



Environmental

- -20 to +40°C. IP55 rated.
- Smart Coldstart®
- Smart Environmentals®
- Smart Exchange®

RDM® – Smart Management & Maintenance



Communication

- Secure global 4G communication
- Immediacy of data exchanges / feeds



Smart Management

- Centralised configuration
- Centralised data collection
- Automated alerts



Smart Reporting

- Full data reporting
- Live and historic
- Client web dashboard
- SLA reporting on KPIs



Smart Monitoring

- Temperatures
- Humidity
- Fans
- Brightness
- Media player / router
- Power
- CMS / RDM® communication



Smart Maintenance®

- Remote fixes
- Trouble ticketing
- On-site maintenance management
- Asset management
- Modular swap-outs



End-to-End Services

- Helpdesk
- Hosting
- SIM management
- Remote updates
- Consultancy