



The Conquest 130W is a high performance IP66 rated street light optimised for high uniformity and maximum spacing's between columns.

Manufactured with anti-corrosion die cast aluminium, stainless steel fixings and featuring high impact glass for additional protection.

Complete with adjustable spigot for side or column top entry, and 10M of cable for a quick installation.

Options include Nema socket, Dali Driver, LED colour temperature, and spigot size.

# Conquest 130W - LED Street Light

## Street Lighting




## Features

- LED rating 17,765lm (4000K)
- LED rating 14,300lm (3000K)
- Luminaire flux 15,100lm (4000K)
- Luminaire flux 12,201lm (3000K)
- -20 to +50°C operating temperature
- LED Life span > 100,000hrs
- Osram LED and Osram Driver
- Post-top or side-entry, 60/76mm spigot options
- Anti-corrosion die cast aluminium
- Corrosion resistant polyester powder coating
- Optimised optics for high uniformity and maximum spacing's between columns
- Future proof design

## Applications

- Roads
- Residential
- Railway Stations
- Shopping Precincts
- Parks & Gardens
- Security



## Specifications

### Conquest 130W

Item Number	Description	Light Source	LED Rating (lm)	Total Wattage(W)	Colour Name	CCT (K)	CRI	Voltage (VAC)	Drive Current	Luminaire Flux (lm)	Luminaire Efficacy (lm/W)	Kg	Unit Colour	Spigot Size (mm)
<b>Standard - Grey - 4K</b>														
CQ130-A6N-00G-60	Conquest-130W-LED-AC-4K-Std-Grey-60mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14	Grey	60
CQ130-A6N-00G-76	Conquest-130W-LED-AC-4K-Std-Grey-76mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14	Grey	76
<b>Standard - Grey - 3K</b>														
CQ130-A6W-00G-60	Conquest-130W-LED-AC-3K-Std-Grey-60mm	LED	14,300	130	WW	3K	Ra>80	220-240	650	12,201	94	14	Grey	60
CQ130-A6W-00G-76	Conquest-130W-LED-AC-3K-Std-Grey-76mm	LED	14,300	130	WW	3K	Ra>80	220-240	650	12,201	94	14	Grey	76
<b>Standard - Grey - Nema Socket - 4K</b>														
CQ130-A6N-06G-60	Conquest-130W-LED-AC-4K-Std-Nema Socket-Grey-60mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14.25	Grey	60
CQ130-A6N-06G-76	Conquest-130W-LED-AC-4K-Std-Nema Socket-Grey-76mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14.25	Grey	76
<b>Standard - Grey - Nema Socket - 3K</b>														
CQ130-A6W-06G-60	Conquest-130W-LED-AC-3K-Std-Nema Socket-Grey-60mm	LED	14,300	130	WW	3K	Ra>80	220-240	650	12,201	94	14.25	Grey	60
CQ130-A6W-06G-76	Conquest-130W-LED-AC-3K-Std-Nema Socket-Grey-76mm	LED	14,300	130	WW	3K	Ra>80	220-240	650	12,201	94	14.25	Grey	76
<b>Dali - Grey - 4K</b>														
CQ130-A6N-20G-60	Conquest-130W-LED-AC-4K-Dali-Grey-60mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14	Grey	60
CQ130-A6N-20G-76	Conquest-130W-LED-AC-4K-Dali-Grey-76mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14	Grey	76
<b>Dali - Grey - 3K</b>														
CQ130-A6W-20G-60	Conquest-130W-LED-AC-3K-Dali-Grey-60mm	LED	14,300	130	WW	3K	Ra>80	220-240	650	12,201	94	14	Grey	60
CQ130-A6W-20G-76	Conquest-130W-LED-AC-3K-Dali-Grey-76mm	LED	14,300	130	WW	3K	Ra>80	220-240	650	12,201	94	14	Grey	76
<b>Dali - Grey - Nema Socket - 4K</b>														
CQ130-A6N-26G-60	Conquest-130W-LED-AC-4K-Dali-Nema Socket-Grey-60mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14.25	Grey	60
CQ130-A6N-26G-76	Conquest-130W-LED-AC-4K-Dali-Nema Socket-Grey-76mm	LED	17,765	130	NW	4K	Ra>70	220-240	650	15,100	117	14.25	Grey	76

# Specifications

## Conquest 130W

Item Number	Description	Light Source	LED Rating (lm)	Total Wattage(w)	Colour Name	CCT (K)	CRI	Voltage (VAC)	Drive Current	Luminaire Flux (lm)	Luminaire Efficacy (lm/w)	Kg	Unit Colour	Spigot Size (mm)
Dali - Grey - Nema Socket - 3K														
CQ130-A6W-26G-60	Conquest-130W-LED-AC-3K-Dali-Nema Socket-Grey-60mm	LED	14,300	130	NW	3K	Ra>80	220-240	650	12,201	94	14.25	Grey	60
CQ130-A6W-26G-76	Conquest-130W-LED-AC-3K-Dali-Nema Socket-Grey-76mm	LED	14,300	130	NW	3K	Ra>80	220-240	650	12,201	94	14.25	Grey	76

Legend: **Std** = Standard. **4K** = Neutral White (4000K). **3K** = Warm White (3000K) **NW** = Neutral White. **WW** = Warm White.